


# OWNER'S MANUAL



## CF-3252-A

### CF-3252-A VERTICAL KNEE RAISE (VKR)



**\*\*WARNING!\*\***

TO PREVENT POSSIBLE TIPPING, BOLT THIS UNIT TO THE EXERCISE FLOOR. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY OR DEATH.

Note: Both Serial Number and Model Number are Required when Ordering Parts

**RECORD SERIAL NUMBER HERE**

**MACHINE CODE**

**A05**

**Customer Service**

(800) 548-5438

(858) 578-7676

**Fax**

(858) 578-9558



[www.facebook.com/hoistfitness](http://www.facebook.com/hoistfitness)

# OWNER'S MANUAL

## CONTENTS

|                                      |    |
|--------------------------------------|----|
| INSTRUCTIONS .....                   | 02 |
| FRAME ASSEMBLY .....                 | 04 |
| PRE-ASSEMBLY.....                    | 14 |
| DECAL PLACEMENT.....                 | 15 |
| DECAL REFERENCE.....                 | 16 |
| PART LIST.....                       | 17 |
| ABBREVIATIONS.....                   | 19 |
| BOLT SIZING CHART.....               | 21 |
| WASHER SIZING CHART.....             | 27 |
| MAINTENANCE SCHEDULE.....            | 29 |
| GENERAL MAINTENANCE INFORMATION..... | 30 |
| WEIGHT TRAINING TIPS.....            | 31 |
| EXERCISE LOG.....                    | 32 |
| LIMITED WARRANTY.....                | 33 |

# **OWNER'S MANUAL**

## **INSTRUCTIONS**

Before beginning assembly please take the time to read instructions thoroughly. Please use the various lists in this manual to make sure that all parts have been included in your shipment. When ordering, use part number and description from the lists. Use only HOIST replacement parts when servicing. Failure to do so will void your warranty and could result in personal injury.

HOIST equipment is designed to provide the smoothest, most effective exercise motion possible. After assembly, you should check all functions to ensure correct operation. If you experience problems, first recheck the assembly instructions to locate any possible errors made during assembly. If you are unable to correct the problem, call your authorized HOIST dealer. Be sure to have your serial number and this manual when calling. When all parts have been accounted for, continue on.

## **TOOLS REQUIRED**

**Ratchet Wrench**

**1/2", 9/16" and 3/4" Sockets**

**Adjustable Wrench**

**Rubber Mallet**

**Tape Measure**

**Level**

**Hex Key Wrench Set**


**Two People**

# OWNER'S MANUAL

\*\*\*THIS PAGE WAS INTENTIONALLY LEFT BLANK\*\*\*

# OWNER'S MANUAL


## FRAME ASSEMBLY



# OWNER'S MANUAL

## FRAME ASSEMBLY


NOTE:  
- HAND TIGHTEN HARDWARE.



# OWNER'S MANUAL

## FRAME ASSEMBLY


NOTE:  
- HAND TIGHTEN HARDWARE.



# OWNER'S MANUAL

## FRAME ASSEMBLY

NOTE:  
- HAND TIGHTEN HARDWARE.






# OWNER'S MANUAL

## FRAME ASSEMBLY

NOTE:  
- HAND TIGHTEN HARDWARE.

**\*\*BACKBONE ASSEMBLY FOR CF-3252-A\*\***

**IMPORTANT!**  
IF ASSEMBLING A FITNESS TREE (CF-3962-A), SKIP  
TO THE ASSEMBLY STEP ON THE NEXT PAGE



# OWNER'S MANUAL


## FRAME ASSEMBLY

NOTE:  
- HAND TIGHTEN HARDWARE.

### \*\*BACKBONE ASSEMBLY FOR CF-3962-A\*\*

**IMPORTANT!**  
FOR CF-3962-A ASSEMBLY, REFER TO  
THE CF-3962-A OWNER'S MANUAL ONCE THIS  
ASSEMBLY STEP IS COMPLETE.


026-01X3739 (UPRIGHT PULL UP ASSEMBLY)  
SHIPPED SEPARATELY WITH CF-3962A-OPT-1



# OWNER'S MANUAL

## FRAME ASSEMBLY

NOTE:  
- WRENCH TIGHTEN HARDWARE.  
- WRENCH TIGHTEN ALL PREVIOUSLY  
HAND TIGHTENED HARDWARE.



### **\*IMPORTANT\***


NOW THAT THE CF-3252-A IS COMPLETELY ASSEMBLED TAKE TIME TO ASSURE THAT YOUR UNIT IS ASSEMBLED SQUARE AND PERPENDICULAR. IF NOT, IT WILL BE NECESSARY TO LOOSEN SOME FRAME HARDWARE TO RE-ALIGN THE FRAME AND RETIGHTEN BOLTS.



# OWNER'S MANUAL

## FRAME ASSEMBLY


NOTE:  
- WRENCH TIGHTEN HARDWARE.  
- SOME PARTS MAY HAVE BEEN REMOVED FOR CLARITY.



# OWNER'S MANUAL


## FRAME ASSEMBLY

NOTE:  
- WRENCH TIGHTEN HARDWARE.  
- SOME PARTS MAY HAVE BEEN REMOVED FOR CLARITY.




# OWNER'S MANUAL

## PRE-ASSEMBLY



# OWNER'S MANUAL

## DECAL PLACEMENT





# OWNER'S MANUAL

## DECAL REFERENCE

**WARNING**

USE ONLY GENUINE REPLACEMENT PARTS. FAILURE TO DO SO WILL VOID WARRANTY AND COULD RESULT IN PERSONAL INJURY OR EVEN DEATH. THERE IS A RISK ASSUMED BY INDIVIDUALS WHO USE THIS TYPE OF EQUIPMENT. TO MINIMIZE THE RISK ALWAYS FOLLOW THESE SIMPLE RULES:

1. READ & UNDERSTAND ALL ENCLOSED INSTRUCTIONS before using this equipment.
2. INSPECT EQUIPMENT BEFORE EACH USE. Replace all parts at the first signs of wear or damage. If in doubt about a certain part, DO NOT use the equipment until the part is replaced. Failure to replace worn or damaged parts may result in injury.
3. FOLLOW ROUTINE MAINTENANCE SCHEDULE
4. CONSULT YOUR PHYSICIAN BEFORE STARTING ANY EXERCISE PROGRAM. Warm up properly before engaging in weight resistance training. Stop exercising if you feel faint or dizzy.
5. TO PREVENT THE POSSIBILITY OF SERIOUS INJURY, KEEP CLEAR OF ALL MOVING PARTS. Do not attempt to free any jammed part by yourself. Obtain assistance in order to avoid possible injury.
6. Take your time and do not rush the exercise. Practice proper breathing. NEVER hold your breath.
7. CHILDREN SHOULD NOT BE ALLOWED TO USE THIS EQUIPMENT WITHOUT ADULT SUPERVISION. To avoid possible injury, bystanders should be kept at a safe distance when this equipment is in use.
8. CALL YOUR AUTHORIZED DISTRIBUTOR if you have any questions on the proper use or maintenance of this equipment.

021-0003135

**NOTICE**

| COMMERCIAL MAINTENANCE   | Daily | Weekly | Monthly | Yearly |
|--|-------|--------|---------|--------|
| Inspect; Links, Pull Pins, Snap Locks, Swivels, Weight Stack Pins              | X     |        |         |        |
| Clean; Upholstery  |       | X      |         |        |
| Inspect; Cables or Belts and their tension                                     | X     |        |         |        |
| Inspect; Accessory Bars and Handles  |       | X      |         |        |
| Inspect; All Decals  |       | X      |         |        |
| Inspect; All nuts and Bolts Tighten if Needed.                                 |       | X      |         |        |
| Inspect; Anti-Skid Surfaces  |       | X      |         |        |
| Clean & Lubricate; Guide Rods with a Teflon (PTFE) based lubricant (SuperLube) |       |        | X       |        |
| Lubricate; Seat Stoves, Turcite Bushings, Linear Bearing                       |       |        | X       |        |
| Clean & Wax; All Glossy Finishes   |       |        |         | X      |
| Repack with Grease Linear Bearings   |       |        |         | X      |
| Replace; Cables, Belts and Connecting Parts.                                   |       |        |         | X      |

021-0003008



**HOIST**  
HOISTFITNESS.COM

1-800-548-5438  
www.hoistfitness.com  
SERIAL # 00-00-A-000000

SERIAL # DECAL

**WARNING**

400 LBS.  
MAXIMUM  
WEIGHT RATING

021-0003226

# OWNER'S MANUAL

## PART LIST

NOTE: SOME OF THESE PARTS MAY COME PRE-INSTALLED

| ITEM NO. | PART NUMBER     | DESCRIPTION                                | QTY. |
|----------|-----------------|--|------|
| 1        | 026-01X3738     | BACK SUPPORT ASSEMBLY                      | 1    |
| 2        | 026-01X5107     | REAR FOOT ASSEMBLY                         | 1    |
| 3        | 026-01X5117     | LOWER SIDE FRAME , LEFT ASSEMBLY           | 1    |
| 4        | 026-01X5118     | SIDE UPRIGHT ASSEMBLY                      | 2    |
| 5        | 026-01X5119     | ARM REST, RIGHT SIDE ASSEMBLY              | 1    |
| 6        | 026-01X5120     | ARM REST, LEFT SIDE ASSEMBLY               | 1    |
| 7        | 026-01X5162     | LOWER SIDE FRAME, RIGHT ASSEMBLY           | 1    |
| 8        | 026-01X1610     | FOOT PLATE ASSEMBLY                        | 4    |
| 9        | 022-01PD2208-A  | ARM PAD ASSEMBLY                           | 2    |
| 10       | 022-01PD2306-B  | BACK PAD ASSEMBLY                          | 1    |
| 11       | 016-0201016     | END CAP 2.00" X 4.00" (BLACK)              | 1    |
| 12       | 026-01F0300     | FLNG-B, .188" X Ø3.00" X 6.25" LG.         | 4    |
| 13       | 026-01F0321     | FLNG-F, .188" x 2.00" x 9.00" LG.          | 2    |
| 14       | 026-01F0515     | FLNG-F, .188" X 4.00" X 9.00" LG.          | 1    |
| 15       | 026-01M0932     | ALUMINIUM CAP: Ø1.25" ID                   | 2    |
| 16       | 026-01M0933     | ALUMINUM RING: Ø1.25" ID                   | 2    |
| 17       | 026-01M0934     | ALUMINUM CAP: Ø1.50" ID                    | 2    |
| 18       | 026-01M0935     | ALUMINIUM RING: Ø1.50" I.D.                | 2    |
| 21       | 026-01PL0209-4A | GRIP OPEN ENDED Ø1.50" X 13.50" LG.        | 2    |
| 22       | 026-01PL0235-17 | GRIP OPEN ENDED Ø1.188" X 5.00" LG.        | 2    |
| 23       | 026-01PL2510    | ELLIPTICAL RUBBER FOOT W/ FRONT LIP & TAPE | 4    |
| 25       | 013-1002010     | 5/16" SAE FLAT WASHER (Ni)                 | 6    |
| 26       | 013-1002007     | 3/8" X 22mm FLAT WASHER (Ni)               | 16   |
| 27       | 013-1002006     | 1/2" X 27mm SAE FLAT WASHER (Ni)           | 24   |
| 28       | 013-1006003     | 3/8" SPLIT LOCK WASHER (Ni)                | 4    |
| 29       | 013-1009002     | 1/2" CURVED WASHER (Ni)                    | 10   |
| 30       | 013-0202007     | 1/2" CURVED WASHER (WZ)                    | 6    |
| 31       | 011-0411001     | SET SCREW: 1/4"-28 X .25" LG. (SS)         | 8    |
| 32       | 011-0701004     | 5/16"-18UNC X 1.25" BHCS (Ni)              | 4    |
| 33       | 011-0701021     | 5/16"-18UNC X 5.00" BHCS (Ni)              | 2    |
| 34       | 011-0701021     | 3/8"-16UNC X 1.25" BHCS (Ni)               | 12   |
| 36       | 011-0116116     | 1/2"-13UNC X 3.25" LOW HEAD SHCS (Ni)      | 4    |

# OWNER'S MANUAL

## **PART LIST CONTINUED**


NOTE: SOME OF THESE PARTS MAY COME PRE-INSTALLED

| ITEM NO. | PART NUMBER    | DESCRIPTION                                 | QTY. |
|----------|----------------|---|------|
| 37       | 011-0116117    | 1/2"-13UNC X 3.50" LOW HEAD SHCS (Ni)       | 4    |
| 38       | 011-0116118    | 1/2"-13UNC X 3.75" LOW HEAD SHCS (Ni)       | 8    |
| 39       | 011-0116123    | 1/2"-13UNC X 5.00" LOW HEAD SHCS (Ni)       | 4    |
| 40       | 012-0504005    | 3/8"-16 UNC THIN NYLOCK NUT (Ni)            | 8    |
| 41       | 012-0504002    | 1/2"-13 UNC THIN NYLOCK NUT (Ni)            | 20   |
| 42       | 021-0003008    | DECAL COMMERCIAL MAINTENANCE 1.50 X 6.69    | 1    |
| 43       | 021-0003135    | DECAL WARNING 1.50" X 6.69"                 | 1    |
| 44       | 021-0003221    | DECAL HOIST 2.50" X 9.13"                   | 4    |
| 45       | 021-0003226    | DECAL 400 LB. WEIGHT RATING 1.625" X 1.625" | 1    |
| 46       | SERIAL # DECAL | DECAL HOIST SERIAL # 1.63" X 2.63"          | 1    |
| 47       | 013-1010003    | 5/16" INTERNAL LOCK WASHER (Ni)             | 6    |


# OWNER'S MANUAL

## ABBREVIATIONS


BZ = Black Zinc  
WZ = White Zinc  
SS = Stainless Steel  
Ni = Nickel Plated




HHB = Hex Head Bolt




FHCS = Flat Head Cap Screw




BHCS = Button Head Cap Screw



SHCS = Socket Head Cap Screw



Low Head SHCS = Low Head Socket  
Head Cap Screw




SHSS = Socket Head Shoulder Screw

# OWNER'S MANUAL




\*\*\*THIS PAGE WAS INTENTIONALLY LEFT BLANK\*\*\*

# OWNER'S MANUAL



## BOLT SIZING CHART HEX HEAD BOLT





1/4" HHB  
RECOMMENDED  
TORQUE RANGE:  
6-8 ft-lbs




5/16" HHB  
RECOMMENDED  
TORQUE RANGE:  
14-17 ft-lbs



3/8" HHB  
RECOMMENDED  
TORQUE RANGE:  
24-30 ft-lbs




1/2" HHB  
RECOMMENDED  
TORQUE RANGE:  
60-75 ft-lbs






# OWNER'S MANUAL



## BOLT SIZING CHART FLAT HEAD CAP SCREW




1/4" FHCS  
RECOMMENDED  
TORQUE RANGE:  
5-7 ft-lbs



3/8" FHCS  
RECOMMENDED  
TORQUE RANGE:  
19-26 ft-lbs



1/2" FHCS  
RECOMMENDED  
TORQUE RANGE:  
47-65 ft-lbs






# OWNER'S MANUAL



## BOLT SIZING CHART BUTTON HEAD CAP SCREW





1/4" BHCS  
RECOMMENDED  
TORQUE RANGE:  
5-7 ft-lbs




5/16" BHCS  
RECOMMENDED  
TORQUE RANGE:  
11-15 ft-lbs



3/8" BHCS  
RECOMMENDED  
TORQUE RANGE:  
19-26 ft-lbs



1/2" BHCS  
RECOMMENDED  
TORQUE RANGE:  
47-65 ft-lbs








# OWNER'S MANUAL



## BOLT SIZING CHART SOCKET HEAD CAP SCREW




1/4" SHCS  
RECOMMENDED  
TORQUE RANGE:  
11-14 ft-lbs



5/16" SHCS  
RECOMMENDED  
TORQUE RANGE:  
23-29 ft-lbs




3/8" SHCS  
RECOMMENDED  
TORQUE RANGE:  
39-49 ft-lbs





# OWNER'S MANUAL

## BOLT SIZING CHART LOW HEAD SOCKET HEAD CAP SCREW





1/4"  
LOW HEAD  
SHCS

RECOMMENDED  
TORQUE RANGE:  
4-6 ft-lbs





5/16"  
LOW HEAD  
SHCS

RECOMMENDED  
TORQUE RANGE:  
9-12 ft-lbs




3/8"  
LOW HEAD  
SHCS

RECOMMENDED  
TORQUE RANGE:  
18-23 ft-lbs



1/2"  
LOW HEAD  
SHCS

RECOMMENDED  
TORQUE RANGE:  
40-50 ft-lbs





# OWNER'S MANUAL



## BOLT SIZING CHART SOCKET HEAD SHOULDER SCREW




1/4" SHSS  
RECOMMENDED  
TORQUE RANGE:  
3-4 ft-lbs



5/16" SHSS  
RECOMMENDED  
TORQUE RANGE:  
8-10 ft-lbs




3/8" SHSS  
RECOMMENDED  
TORQUE RANGE:  
17-22 ft-lbs




# OWNER'S MANUAL

## WASHER SIZING CHART


013-0002003  
1/4"  
FLAT WASHER  
SMALL, SAE, 13mm




013-0102004  
5/16"  
FLAT WASHER  
LARGE, USS, 22mm




013-0002004  
3/8"  
FLAT WASHER  
SMALL, SAE, 21mm




013-0402005  
3/8"  
FLAT WASHER  
LARGE, USS, 25mm




013-0102003  
1/2"  
FLAT WASHER  
SMALL, SAE, 27mm




013-0102026  
1/2"  
FLAT WASHER  
LARGE, USS, 34mm



013-0102028  
3/8"  
CURVED WASHER




013-0402007  
3/8"  
FLAT WASHER  
22mm O.D.




013-0102019  
1/4"  
LOCK WASHER





013-0102020  
3/8"  
LOCK WASHER



013-0102018  
1/2"  
LOCK WASHER




014-0018001  
1/2" LONG  
SPACER




026-01M0238  
2" ALUMINUM  
FLATHEAD CAP


016-0009003  
1" SHIM WASHER




013-0003002  
3/8" FENDER WASHER




013-0003004  
1 1/16"  
FENDER WASHER



026-01PL151  
PLASTIC 1 1/16"  
FENDER WASHER




014-0018002  
1" LONG  
SPACER




# OWNER'S MANUAL

## WASHER SIZING CHART (CONTINUED)


026-01M0211  
1/4" LONG  
FLANGED SPACER




026-01M0198  
1/2" LONG  
FLANGED SPACER




026-01M0760  
1/2" LONG HEAVY  
FLANGED SPACER




026-01M211T  
1/4" LONG HEAVY  
FLANGED SPACER




026-01M0532  
11/16" LONG HEAVY  
FLANGED SPACER




026-01M0551  
1" LONG HEAVY  
FLANGED SPACER




026-01M0788  
.81" LONG HEAVY  
FLANGED SPACER




026-01M0780  
.65" LONG HEAVY  
FLANGED SPACER




026-01M0761  
1 11/16" LONG HEAVY  
FLANGED SPACER




026-01M0789  
.44" LONG HEAVY  
FLANGED SPACER




026-01M0762  
1 1/2" LONG HEAVY  
FLANGED SPACER




026-01M0768  
1 1/4" LONG HEAVY  
FLANGED SPACER




026-01M0600  
.625" LONG  
FLANGED SPACER



026-01M0240  
1 3/8" ALUMINUM  
FLATHEAD CAP



026-01M0239  
1 5/8" ALUMINUM  
FLATHEAD CAP



# OWNER'S MANUAL

## MAINTENANCE SCHEDULE

| ROUTINE  | COMMERCIAL /<br>LIGHT COMMERCIAL<br>MAINTENANCE | HOME<br>MAINTENANCE | LATEST DATE ENTRY |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|---|---------------------|-------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Inspect;<br>Links, Pull Pins, Snap Locks,<br>Swivels, Weight Stack Pins              | DAILY   | WEEKLY              |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Clean;<br>Upholstery   | DAILY   | WEEKLY              |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Inspect;<br>Cables or Belts and their<br>tension                                     | DAILY   | WEEKLY              |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Inspect;<br>Accessory Bars, and Handles  | WEEKLY  | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Inspect;<br>All Decals   | WEEKLY  | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Inspect;<br>All Nuts and Bolts, Tighten if needed                                    | WEEKLY  | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Inspect;<br>Anti-Skid Surface  | WEEKLY  | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Clean & Lubricate;<br>Guide Rods with a Teflon (PTFE)<br>based lubricant (Superlube) | MONTHLY   | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Lubricate;<br>Seat Sleeves, Turcite Bushings,<br>Linear Bearing                      | MONTHLY   | 3 MONTHS            |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Clean and Wax;<br>All Glossy Finishes  | 6 MONTHS  | YEARLY              |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Repack with Grease;<br>Linear Bearings   | 6 MONTHS  | YEARLY              |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| Replace;<br>Cables, Belts and Connecting Parts                                       | YEARLY  | 3 YEARS             |                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

*Your equipment comes with a commercial maintenance decal.  
For personal, in home use, please follow the home maintenance schedule listed above.*

***Never use ammonia, acid-based, or petroleum-based solvents on any portion of the machine as it may damage the finish.***

# OWNER'S MANUAL

## **HOIST FITNESS SYSTEMS** **GENERAL MAINTENANCE INFORMATION**

### **Links, Pull-Pins, Snap Hooks, Swivels, Weight Stack Pins:**

- \*Check all pieces for signs of visible wear or damage.
- \*Check springs in snap hooks and pull-pins for proper tension and alignment.
- \*If the spring sticks or has lost its rigidity, replace it immediately.

### **Upholstery:**

- \*To ensure prolonged upholstery life and proper hygiene, all upholstered pads should be wiped down with a damp cloth after every workout.
- \*Periodically take the time to use a mild soap or an approved vinyl upholstery cleaner to deter the onset of cracking or drying. Avoid using any abrasive cleaners or cleaners not intended for use on vinyl.
- \*Replace ripped or worn upholstery immediately.
- \*Keep sharp or pointed objects clear of all upholstery.

### **Decals:**

- \*Inspect and familiarize yourself with any safety warnings or other user information posted on each decal.

### **Nuts and Bolts:**

- \*Inspect all nuts and bolts for any loosening and tighten if needed.
- \*Go through a re-tightening sequence periodically to ensure that all hardware is tensioned proper.

### **Anti-Skid Surfaces:**

- \*These surfaces are designed to supply secure footing and need to be replaced if they appear worn or become slippery.

### **Belts and Cables:**

- \*Hoist uses only high quality belt, and mil-spec cables.
- \*Visually inspect the belts and cables for fraying, cracking, peeling or discoloration.
- \*While the machine is not in use, carefully run your fingers along the belt or cable to feel for thinning or bulging areas.
- \*Replace belts and cables immediately at the first signs of damage or wear. Do not use equipment until belts or cables have been replaced.

### **Belt and Cable Tension:**

- \*Referring to the Owners Manual, when belts or cables are used check all bolts attachments to be sure they are properly attached.
- \*Check slack in cables and re-adjust cable tension if needed.

### **Seat Sleeves, Guide Rods:**

- \*Wipe down adjusting tubes with a dust free rag before applying lubricant.
- \*Lubricate seat sleeves and Guide Rods with a Silicon or Teflon based lubricant spray.

### **Linear Bearings:**

- \*Referring to the Owners Manual carefully disassemble the bearing from its housing and place a finger full of light grease (lithium, super lube, etc.) into the inside of the bearing. Using your finger, press the grease into the ball-bearings and their tracks. repeat until the ball-bearing tracks are full of grease. Insert the shaft back into the bearing and wipe off excess grease.

**PLEASE KEEP THIS FOR YOUR RECORDS**

# OWNER'S MANUAL

## WEIGHT TRAINING TIPS

Use this manual to guide you through the basic exercises you can perform on your CF-3252-A HOIST® Fitness System. To gain maximum results and avoid possible injury, consult a fitness professional to develop your complete exercise program.

Always consult your physician before starting any exercise program.

To be successful in your exercise program, it is important to develop an understanding of the basic principles of strength training. Now that you have your CF-3252-A HOIST® Fitness System, it is only natural that you want to get started immediately. First, determine a set of realistic goals and objectives for yourself. By deciding on an exercise plan that is right for you prior to starting, you will contribute significantly to your success.

Warm up properly before engaging in weight resistance training. Stretching, yoga, jogging, calisthenics or other cardiovascular exercise can help prepare your body for the heavier workload of lifting weights.

Learn how to perform the exercise correctly before using heavy weight. Correct form is important to avoid injury and to ensure that you work the proper muscle groups.

Know your limitations. If you are new to weight training or are embarking on an exercise regimen after a long layoff, start slowly and build foundational strength over a longer period of time.

Pay attention to your breathing. Exhale when you exert is a general rule of thumb. Never hold your breath.

**Enjoy your CF-3252-A HOIST® Fitness System!**





# OWNER'S MANUAL

## **HOIST FITNESS SYSTEMS** **LIMITED LIFETIME WARRANTY**

Hoist Fitness Systems warrants this product to the **original purchaser** to be free from defects in workmanship and/or materials under normal use or service. If at any time a component part is defective, Hoist Fitness Systems shall repair or replace it (at Hoist Fitness Systems option) within a reasonable period of time. This warranty does not cover costs of removal, transportation or reinstallation. This warranty shall not apply if the defect was caused by misuse, neglect or normal wear and tear.

**WARRANTY CLAIMS. All claims require: Model number, Serial number, Date of installation, and any information supporting the existence of the alleged defect.**

**To complete Warranty Registration visit:**

**[www.HOISTFITNESS.com](http://www.HOISTFITNESS.com)**

**and click on the Warranty Registration link**

Starting from the original date of purchase, normal wear and tear shall be considered as the following:

**COMMERCIAL USE:** All malfunctions of upholstery, grips, and coatings that occur up to one year; all malfunctions of belts, or cables up to one year; all malfunctions of pulleys, bearings, or bushings that occur up to three years. The frame and body components are warranted for ten years, with structural moving parts warranted for five years.

**LIGHT COMMERCIAL USE:** All malfunctions of upholstery, grips, and coatings that occur up to one year; all malfunctions of belts, or cables up to one year; all malfunctions of pulleys, bearings, or bushings that occur up to three years. The frame and body components are warranted for ten years, with structural moving parts warranted for five years.

**HOME USE:** All malfunctions of grips, paint, and chrome that occur up to ten years; all malfunctions of electronic components, belts, cables, or upholstery that occur up to ten years; all malfunctions of pulleys, bearings, or bushings that occur up to ten years. The frame and all welded components are warranted for the life of the product.

**PLEASE NOTE THAT NOT ALL HOIST PRODUCTS ARE MADE FOR COMMERCIAL USE.** Refer to the instructions page of your owners manual or consult with you fitness product dealer to establish if a product is made for commercial use or not. Using a non-commercial product in a commercial setting can result in serious injury or death! Hoist Fitness Systems sole responsibility shall be to repair or replace the component within the terms stated above. Hoist Fitness Systems shall not be liable for any loss or damage of any kind including any incidental or consequential damages resulting, directly or indirectly from any warranty expressed or implied or any other failure of this product.

**LIGHT COMMERCIAL USE:** Our Light Commercial warranty applies to facilities that **DO NOT** charge monthly membership dues and where the equipment would be used by **no more than 50** people per day. Examples of Light Commercial facilities include hotels, apartment complexes, personal training studios, fire stations, police stations, etc., that meet the criteria stated above.

**WHAT IS NOT COVERED BY THIS WARRANTY:** Hoist's sole obligation under this warranty is limited to either repair or replacement of parts, subject to the additions below. This warranty neither assumes nor authorizes any person to assume obligations other than expressly covered by this warranty.

**NO CONSEQUENTIAL DAMAGES:** Hoist is not responsible for economic loss; profit loss; or special, indirect, or consequential damages.

**WARRANTY IS NOT TRANSFERABLE:** This warranty is not assignable and applies only in favor of the original purchaser/user to whom delivered. Any such assignment or transfer shall void the warranties herein made and shall void all warranties, expressed, implied or statutory, except the one (1) and five (5) year warranties described above. These warranties are exclusive and in lieu of all other warranties, including implied warranty and merchantability or fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.

**TRANSPORTATION COSTS:** Hoist will accept parts covered under this warranty freight collect, provided that shipment has received prior approval. Hoist is not responsible for any other transportation costs, but will ship freight collect parts either repaired or replaced under these warranties.

Hoist Fitness Systems  
11900 Community Rd.  
Poway, CA. 92064  
(800)548-5438

**PLEASE KEEP THIS FOR YOUR RECORDS**